88VX Series <u>Airline Respirator</u>



The Bullard 88VX Series airline respirators offer advancements in comfort and reliable respiratory protection for abrasive blasters and painters. The 88VX Respirator is NIOSH approved as a Type C and CE Continuous Flow Class Respirator (Approval No. TC-19C-293).

Advanced Protection

- Sewn-in neck cuff provides a physical barrier to airborne contaminants
- Double lining in the neck area enhances durability and protection

Comfortable Fit

- Lightweight inner shell with an adjustable headband suspension
- · Airflow is channeled directly to the user's breathing zone
- No fit testing required
- Optional cheek pads for increased stability

Head Protection

- · Helmet provides top impact and penetration protection
- Helmet and cape help protect the worker's entire head, face, and upper body from abrasive rebound, airborne contaminants and messy overspray

Optimum Visibility

- Wide-angle faceshield lens
- Translucent yellow helmet prevents closed-in feeling among workers
- Optional tinted lenses provide protection from the sun

Climate Control

• Optional climate control devices warm or cool incoming air to maximize comfort and improve productivity









88VX Series Airline Respirator

88VX Parts List

88VXSYS

Includes a 88VX3235 respirator assembly, ADP20 Free -Air® pump, 50 foot (15 m) air supply hose and Frigitron 2000 climate control device.						
	Respirator Models For use with breathing air compressors Includes EVX30 breathing tube assembly with 1/4" Industrial Interchange fitting and					
	outer lenses and cape. Breathing air supply hose not included.					
88VX3230	Respirator with 46VX nylon cape -28° (71 cm) length					
88VX3230H	Same as model 88VX3230 with 25' (8m) of starter hose					
88VX1330	Same as model 88VX3230 with 13VX nylon cape – 38" (96cm) length					
	For use with Bullard Free-Air [®] Pumps					
	\overline{b} breathing tube assembly with $1/2$ " Industrial Interchange fitting and					
	outer lenses and cape. Breathing air supply hose not included.					
88VX3235	Respirator with 46VX nylon cape -28° (71 cm) length.					
88VX3235H100						
	t Capes for 88VX Series Airline Respirators					
	n Cape – 28" (71 cm) length					
	in Cape – 38" (96 cm) length					
	Gate" Style, Tan Nylon Cape – 38" (96 cm) length					
	36VX Hibernia Parka, Tan Nylon Parka with Long Sleeves – 38" (96 cm) length					
	Parka, Tan Nylon Parka with Long Sleeves – 38" (96 cm)length, XL					
	for 88VX Series Airline Respirators					
88VXTGP	Adjustable headband suspension with Plenum					
88VXRTP	Adjustable Sure-Lock® ratchet headband suspension with Plenum					
88VXAK	Oval Door/Gasket/Latch Kit					
88CA	Carrying Strap					
88VXBAIL	Replacement Bail for Latch Assembly (10/pkg)					
88VXHP	Replacement Hinge Pins for Latch Assembly (10/pkg)					
	Elastic Chin Strap					
88CK	Breathing Tube Connector Kit					
BFW	Box Front Window Frame					
77GLT	Box Front Glass Lens					
77LG	Front Box Lens Gasket					
G4613	Rectangular Window Gasket					
G7713	Oval Window Gasket					
GVXCP	Replaceable Cheek Pads, Pair					
88VXOLG	Outer lenses .042", Pack of 25 - Tinted Green					
88VXOLT	Outer lenses .030", Pack of 25 - Tinted Smoke					

Replacement Lenses for 88VX Series (Oval)				
	P771B/B771B	Inner plastic lens, .040" (1 mm) thick (200/pkg)		
	B771040	Outer plastic lens, .040" (1 mm) thick (200/pkg)		
	P771020/B77102	20 Outer plastic lens, .020" (0.5 mm) thick (400/pkg)		
	P771R	Outer plastic lens, .015" (0.4 mm) thick (50/pkg)		
	88VXLC	Clear Mylar lens cover, perforated edges (25/pkg)		
Replacement Breathing Tube Assemblies				
Includes breathing tube, airflow control, quick-disconnect fitting and belt.				
	88VXBT	Breathing tube only (fitting not included)		
	Optional Climate	Control Breathing Tube Assemblies		
		Cool tube with 1/4" Industrial Interchange, steel quick-disconnect		
		fitting. Adjustable airflow. For use with breathing air compressors.		
	HC2400	Hot/Cold tube with 1/4" Industrial Interchange, steel quick-		
		disconnect fitting. Adjustable airflow. For use with breathing air		
		compressors.		
	Frigitron 2000	Cool tube with 1/2" Industrial Interchange, steel quick-disconnect		
		fitting. Adjustable airflow. For use with Bullard ADP20 or EDP30		
		pumps.		
	DC5040	Dual-CooL with 1/4" Industrial Interchange for use with air		
		compressors. Order Dual-Cool vests separately.		
	DC70ML	Dual-Cool vest. Size M/L		
DC70XLXXL Dual-Cool vest. Size XL/XXL		Dual-Cool vest. Size XL/XXL		
CT30 Plastic Cool tube with 1/4		Plastic Cool tube with 1/4" Industrial Steel, quick-disconnect fitting,		
		adjustable airflow. For use with breathing air compressors.		
	HCT30	Plastic Hot/Cold tube with 1/4" Industrial Interchange, steel quick-		
		disconnect fitting. Adjustable airflow. For use with breathing air		
		compressors.		
		oses and Fittings		
		er and Extension Hose Kits (For use with Breathing Air Compressors)		
	Includes 3/8" (10 mm) I.D. rubber hose, V11 hose-to-hose adapter fitting and V13			
		3/8" (10 mm) hose-to-3/8" (10 mm) pipe.		
	4696	25' (8 m) Starter hose kit with 1/4" Industrial Interchange, steel		
	5454	quick-disconnect fittings 25' (8 m) Extension hase kit		

	quick-disconnect fittings				
5454	25' (8 m) Extension hose kit				
5457	50' (15 m) Extension hose kit				
5458	100' (31 m) Extension hose kit				

V20 Series Starter Hoses (For use with Free-Air Pumps) Includes 1/2" (13 mm) I.D. rubber hose with 1/2" Industrial Interchange male/female quick-disconnect coupler.

)50ST 50' (15 m))100ST 100' (31 m)



Americas: Bullard 1898 Safety Way Cynthiana, KY 41031-9303 • USA Toll-free within USA: 877-BULLARD (285-5273) Tel: +1-859-234-6616 Fax: +1-859-234-8987 Europe: Bullard GmbH Lilienthalstrasse 12 53424 Remagen • Germany Tel: +49-2642 999980 Fax: +49-2642 9999829

www.bullard.com

Asia-Pacific: Bullard Asia Pacific Pte. Ltd. LHK Building 701, Sims Drive, #04-03 Singapore 387383 Tel: +65-6745-0556 Fax: +65-6745-5176



©2013 Bullard. All rights reserved. Free-Air is a registered trademark of Bullard. Mylar is a registered trademark of Dupont Teijin Films. 8017 (0613)