

## 1000AV SERIES

## FABRIC BRAID REINFORCED THERMOPLASTIC PAINT HOSE



A high pressure semi-conductive thermoplastic hose that will not swell or degrade when in contact with most paints, chemicals, oils, and solvents. Extremely durable and lightweight. Ideal for situations where electrostatic charge must be dissipated.

**CONSTRUCTION:**

**Inner:** Seamless Nylon Liner

**Outer:** Abrasion and Chemical Resistant Polyurethane Cover

COUPLING CAPABILITIES: NPT, NPSM, JIC Plated or Stainless Steel – M or F

CRP PART NUMBER	COLORS	# OF BRAIDS	NOMINAL I.D. Inches (MM)	NOMINAL O.D. Inches (MM)	MINIMUM BEND RADIUS Inches (MM)	DYNAMIC WORKING PRESSURE	MAXIMUM BURST PRESSURE	MAXIMUM WEIGHT (LBS/FT)	LENGTH	TEMPERATURE RANGE
1003AV	■	1	1/8 (3.2)	0.32 (8.1)	1.25 (31.8)	3,500 psi	14,000 psi	0.03	4" up to 500'	0 to +180°F
1004AV	■	2	3/16 (4.8)	0.43 (10.9)	1.75 (44.5)	3,500 psi	14,000 psi	0.05	4" up to 500'	0 to +180°F
1006AV	■ ■	2	1/4 (6.4)	0.49 (12.5)	2.50 (63.5)	3,300 psi	13,200 psi	0.05	4" up to 500'	0 to +180°F
1010AV	■ ■	2	3/8 (9.5)	0.72 (18.2)	3.00 (76.2)	3,300 psi	13,200 psi	0.11	4" up to 500'	0 to +180°F