## AIRMIX® 20.25 PUMP - STAINLESS STEEL

Ideal for feeding one or two Airmix® spray guns or one gun in a heated circulation loop for small to medium production shop, the 20.25 can pump a variety of coatings. The pump comes with the pump regulator, atomization regulator and filter.

FEATURES	BENEFITS
Large diameter suction rod and high compression ratio	Use with a large number of materials
All stainless steel construction	Compatible with water-based materials
Simple design, reduced number of spare parts	Easy maintenance

SPECIFICATIONS				
Pressure ratio		20/1		
Fluid volume per cycle (cm³)		50		
Number of cycles per liter of products		20		
Fluid Output at 30 cycles/mn (I/mn)		1.5		
Free flow rate (L/mn)		0.79 gal/mn / (3 L/mn)		
Air consumption at 30 cycles/mn at 60 ps	si (4 bar)	6.3 cfm / (10.8 m³/h)		
Maximum air inlet pressure		87 psi / (6 bar)		
Maximum fluid pressure		1800psi / (120 bar)		
Maximum Fluid Temperature		140°F / (60°C)		
Sound level (dBA)		78		
Sealing Packings	Upper sealing	Polyfluid + PTFE G		
	Lower sealing	GT sealing		
Weight		37.5 lb / (17 kg)		
Wetted parts		Stainless steel		
Height		33" / (83.8 cm)		
Width		14" / (35.6 cm)		
Depth		7" / (17.8 cm)		



Model shown on a two-arm cart

FITTINGS			
Fitting	Air inlet (valve)	F 3/8" BSP	
	Air outlet (atomization air)	M 1/4" NPS	
	Fluid Inlet	M 26 x 125	
	Fluid output (filter)	M 1/2" JIC	

CUNFIGURAL	IUN OF AIRIVITA	20.25 PU	VIPS			
Set-up	Suction rod	Drain rod	Atomization air regulator	Fluid pressure air regulator	Pump output filter	Part number
Wall mounted		Yes			Yes	151-773-100
Wall mounted	Yes		Yes	Yes		151-773-200
1 arm cart-mounted		Yes			Yes	151-773-150

SEAL KITS	
Description	Part number
Seal kit for 25 GT	144-950-097
Repair kit for 25 GT	144-950-098
Seal kit for 500-4 air motor	146-260-990
Repair kit for 500-4 air motor	146-260-995

KITS FOR AIRM	IX®20.25 PU	MPS WITH SWIV	EL FITTING XCIT	E			
Kit description	Gun type	Aircap Type	Tip	Hose length	Pump output filter	Part number	
20.25 Wall-mounted	Xcite120		) W 04 K I D # D	Please specify			668-773-100
20.25 Cart-mounted		VX 24 K HVLP (See table 25' / (7.5 m on page 11)	25' / (7.5 m)	Yes	668-773-150		